

Technical Data Sheet



6-axis industrial robot HORST1400

Basic data

Number of axes	6
Maximum payload	10 kg ¹
Nominal load	7 kg
Maximum range	1400 mm
Repeatability	+/- 0,05 mm
Protection classification	IP54
Sound level	< 75 dB
Weight	ca. 75 kg
Installation area	454 x 454 mm
Standard color	RAL 5021 (water blue)
Power supply	230 VAC, 50-60 Hz, 450 W/600 W
Ambient temperature	5-40 °C

Axis data

Axis	Range of movement	Speed ²
1	+176°/-176°	180°/s
2	+86°/-16°	90°/s
3	+42°/-67°	120°/s
4	+171°/-171°	240°/s
5	+119°/-119°	240°/s
6	+300°/-300°	240°/s

¹ Depending on load distances and speed.

² The specified speeds apply for a payload of 3 kg.

Control and interfaces horstCONTROL

Dimensions (H x B x T)	313 mm x 174 mm x 446 mm
I/O connections on switch cabinet	16 digital inputs 14 digital outputs Enhancements possible.
I/O connections on tool flange	2 digital inputs and outputs
I/O power supply	24 V/3 A at control 24 V/2 A at tool flange
Communication	TCP/IP 100-Mbit/s Ethernet [Web-Interface via HTTP]
Safety-relevant interfaces	Emergency stop [input and output] Safety stop [input and output] in accordance with DIN EN ISO 10218-1
Fieldbus	Modbus/TCP Optional: Profinet
Wiring of HORST	Cable between robot and control: 3 m
Wiring of the control unit	Cable between control unit and control: approx. 5 m / 10 m

Programming horstFX

Software	horstFX user interface: simple graphic programming, advanced textual programming and intelligent features. Can be updated.
Control unit	13.3-inch touchscreen with emergency stop, three-level enabling switch and two USB interfaces
Mount	Fixture for mounting the control unit on the wall, table or cell



fruitcore robotics GmbH
Macairestraße 3
78467 Konstanz

T. +49 7531 94599 20
E. info@fruitcore.de
www.fruitcore-robotics.com

Version: V 200909
© fruitcore robotics GmbH